IN THE CLAIMS:

1   1.   (Currently Amended) A method for generating and processing data for the display

2   of a stream of video data on a display screen connected to data processing apparatus, said method

3   comprising the steps of:

4   processing a motion picture expert group compliant data stream of video data selected

5   to be viewed by a user in a first format via said apparatus, the largest frames of said video data

6   known as I frames;

7   pre-filling a buffer memory in the apparatus with a first threshold level of video data

8   prior to decoding said video data, the user viewing the same in the first format;

9   ~~generating an altered format for said video data, wherein the altered format is a fast~~

10   ~~cue or fast forward review video display;~~

11   a user selecting with selection means to view said video data in an ~~said~~ altered format,

12   and in response;

13   ~~following the user selection of the altered format,~~ changing the required level of video

14   data to be held in said buffer memory for the altered format to a second threshold level; ~~and~~

15   wherein at the second threshold level the buffer memory substantially accommodates

16   no more video data than that corresponding to a single I frame, plus a small tolerance percentage

17   value;

18   filling the buffer memory with video data corresponding to a single I-frame; and

19   thereby generating an altered format for said video data, wherein the altered format

20   is a fast cue or fast review video display.

1   2.   (Previously Presented) A method according to Claim 1 wherein the second threshold

2   level is used in identifying a value of the separation of the encoded frames in the video data bitstream

3   and this value is used as a substitute for various header field values of the motion picture expert

4   group data stream which may be unavailable.

1   3.   (Cancelled)

1   4.   (Cancelled)

1   5.   (Previously Presented) A method according to Claim 1 wherein the second threshold

2   level is set at a value to minimize delay in the transition between the generation of video from the

3   normal and altered video formats.

1   6.   (Previously Presented) A method according to Claim 1 wherein the second threshold

2   level of the buffer memory data is estimated by reference to time stamp data transmitted as part of

3   the video data.

1   7.   (Previously Presented) A method according to Claim 6 wherein said time stamp data

2   is carried as part of the systems layer and allows data in the other levels to be time synchronized by

3   referring to and retrieving a common reference time from said time stamp data.

1   8.   (Previously Presented) A method according to Claim 6 including the use of said time

2   stamp data to estimate the size of the I frame data and hence the second threshold level.

1 9. (Previously Presented) A method according to Claim 1 wherein said video data

2 having been transmitted from a location remote to the apparatus is received by the apparatus.

1 10. (Previously Presented) A method according to Claim 9 wherein said apparatus is a

2 broadcast data receiver connected to receive data from a broadcaster.

1 11. (Currently Amended) A method of generating a video display in a first standard

2 motion picture expert group format and a second user selectable fast forward or fast cue format, said

3 method comprising the steps of:

4 upon user selection of a the fast forward or fast cue format during generation of the

5 display in the first format, obtaining a value indicative of the separation of received encoded frames

6 in a video data bitstream;

7 using said value as a replacement value to indicate a new threshold level of data to

8 be held in a buffer memory device prior to the commencement of the decoding;

9 filling the buffer memory device with video data corresponding to a single I-frame;

10 displaying of the first frames of data for the fast forward or fast cue display; and

11 wherein said new threshold level of data is substantially no more than that

12 corresponding to the single largest frame in said video data bitstream plus a small tolerance

13 percentage value.

1 12. (Previously Presented) A method of generating a video display as set forth in Claim

2 11 including the additional step of referring to time stamp data transmitted as part of said video data

3 to estimate said new threshold level of data.

4